

PORCELAIN SUSPENSION TYPE INSULATORS

PORCELAIN SUSPENSION TYPE INSULATORS					
Porcelain Suspension Type Insulators for systems from 115 kV up to 400 kV according to CFE 52210-02 specification. Fujian trademark.					
Short description		25SPC111C	25SPC111CC	28SPC111CC	29SPC160C
Power frequency Flashover Voltage	Dry (kV)	91	107	107	89
	Wet (kV)	58	63	63	59
Critical Impulse Flashover Voltage	Positive (kV)	138	188	188	129
	Negative (kV)	150	169	169	145
Radio-interference Voltage	Power frequency voltage test	10	10	10	10
	Max. RIV at 1 MHz	7	8	8	10
Power frequency Puncture Voltage		148	154	154	160
Mechanical strength		141	141	141	160
Mechanical Impact Strength		8.9	10	10	10
Mechanical routine load 3 seconds (kN)		55.5	55.5	55.5	80
Rated Diameter (mm)		254	280	280	298
Spacing (mm)		146	146	146	146
Min. Creepage Distance (mm)		292	480	480	333

PHONE NUMBER: ☎ 462 625 5833 / 462 625 1093 📞 462 252 8893

www.eprecsa.mx

E-MAIL: ventas@eprecsa.mx

