

COMPOSITE LINE POST INSULATORS

Short description		13PCHG4	22PCHG4	33PCHG4	69PMHG3 / 69PAHG3	115PAHG1	115PAHG2	115PAHG3	9134522- 00	138PAHG1	138PAHG2	138PAHG3	115PMHG1	115PMHG2	115PMHG3
Rated System Voltage (kV)		13.8	23	34.5	69	115	115	115	132	138	138	138	115	115	115
Max. Design Voltage (kV)		15.5	27	38	72.5	123	123	123	-	145	145	145	123	123	123
Power frequency Flashover Voltage	Dry (kV)	70	95	125	250	435	435	435	-	485	485	485	435	435	435
	Wet (kV)	40	65	95	225	390	390	390	410	435	435	435	390	390	390
Critical Lightning Impulse Flashover Voltage	Positive (kV)	110	150	200	350	550	550	550	730	650	650	650	550	550	550
Max. Radio-interference Voltage to 500 kHz (µV)	Voltage test 60 Hz	15	22	30	44	73	73	73	88	88	88	73	73	73	73
	Max. Value	<100	<100	<200	200	200	200	200	200	200	200	200	200	200	200
Min. Creepage Distance (mm)		465	800	1178	2245	2460	3075	3813	3930	2900	3625	4495	2460	3075	3813
Mechanical Strength to bending (minimum)		12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5

PHONE NUMBER: ☎ 462 625 5833 / 462 625 1093 📞 462 252 8893

www.eprecsa.mx

E-MAIL: ventas@eprecsa.mx

