

GROUND MOUNT KIOSK

Part number	GMK15-16-1310 / GMK15-16-2310	GMK27-12-1310 / GMK27-12-2310	GMK38-12-2300	GMK38-16-2300
Current transformer	3 pcs	3 pcs	3 pcs	3 pcs
Voltage sensor	6 pcs	6 pcs	6 pcs	6 pcs
Control type	RC10	RC10	RC10	RC10
Maximum rated voltage	15.5 kV	27 kV	38 kV	38 kV
Rated DC current	630 A	630 A	630 A	630 A
Maximum RSM fault capacity	16 kA	12.5 kA	12.5 kA	16 Ka
Maximum fault capacity (50 Hz)	40 kA	31.5 kA	31.5 kA	40 kA
Maximum fault capacity (60 Hz)	42 kA	32.5 kA	32.5 kA	42 kA
Symmetrical interrupting capacity	16 kA	12.5 kA	12.5 kA	16 kA
Mechanical operations / Full load	30,000	30,000	30,000	30,000
Interrupting capacity operations	70	140	100	140
Short-duration fault current	16 kA/3seg	16 kA/3seg	12.5 kA/3seg	16 kA/3seg
Main interruption capacity	630 A	630 A	630 A	630 A
Cable load current	24 A	25 A	40 A	40 A
Line load current	5 A	5 A	5 A	5 A
Basic Impulse Insulation Level (BIIL)	110 Kv	150 kV	150 kV	150 Kv
Switching impulse	110 kV	150 kV	170 kV	170 Kv
Applied voltage resistance phase to ground (dry)	50 kV	60 kV	70 kV	70 kV
Voltage withstand across switch	50 kV	60 kV	70 kV	70 kV
Room temperature	-40°C a +55°C	-40°C a +55°C	-40°C a +55°C	-40°C a +55°C
Humidity	0 - 100%	0 - 100%	0 - 100%	0 - 100%
Altitude	3000 m	3000 m	3000 m	3000 m
Kiosk mass - GMK 1000	480 kg	480 kg		
Kiosk mass - GMK 2000			1800 kg	1800 kg

PHONE NUMBER: ☎ 462 625 5833 / 462 625 1093 📞 462 252 8893

www.eprecsa.mx

E-MAIL: ventas@eprecsa.mx

